



# VINKOPLAST-MR

## Mould Release Agent

Mould Release Agent

<b>Description</b>	<b>Vinkoplast-MR</b> is a specially formulated blend of mineral oils and selective additives, it is supplied as a low viscosity, pale straw color liquid
<b>Features and benefits</b>	<ul style="list-style-type: none"> <li>■ Can be safely used inside or outside.</li> <li>■ Produces a better and cleaner cast when applied on pre-stressed and precast concrete forms.</li> <li>■ Cuts stripping time to an absolute minimum.</li> <li>■ Reduces form cleaning and repairing.</li> <li>■ Increases wood form life, rustproofs metal forms.</li> <li>■ Effectively minimizes concrete buildup on pavers, R/M trucks, mixers, spreader-finishers, buggies, chutes, and other equipment.</li> <li>■ Breaks concrete bond between surface and form cleanly and effectively leaves smooth surface.</li> <li>■ Will not stain or discolor concrete and can be painted over.</li> <li>■ Ready to use, requires no additional mixing.</li> <li>■ Minimizes surface voids. VOC compliant</li> </ul>
<b>Application instruction</b>	Spraying is the ideal method of application for Vinkoplast-MR . It may also be applied by roller coating, mopping, or brushing. A thin film should be applied for maximum economy and efficiency. Runs or puddles need to be brushed out. For metal forms, the best results are obtained with a spray-on "fog" application of Vinkoplast-MR .
<b>Preparation</b>	<b>Surface Preparation</b> Form surfaces are to be thoroughly cleaned prior to application. All rust, scale, and previously used form release agents must be removed in accordance with good concrete practices
<b>Packaging</b>	210L drum & 25L gallon
<b>Coverage</b>	20-60 m <sup>2</sup> /litre
<b>Precautions</b>	KEEP FROM FREEZING. DO NOT OVER-APPLY Vinkoplast-MR TO FORMS AND EQUIPMENT. DO NOT DILUTE. Surface tensions of certain plastic forms may prevent adequate "wetout" of Vinkoplast-MR. A small test patch application is recommended to ensure uniform coverage of Vinkoplast-MR. If, after application, Vinkoplast-MR exhibits beads on the surface, it is recommended to break the beads with a cheese cloth or brush.
<b>Health and safety</b>	<ul style="list-style-type: none"> <li>■ Avoid Contact with eyes and skin. If skin contact occurs, wash skin thoroughly</li> <li>■ Wear Protective gloves and eye protection during work</li> <li>■ If In eyes, hold eyes open, flood with warm water and seek medical attention immediately</li> </ul>
<b>Limited Warranty</b>	All recommendations, statements and technical data herein are based on tests we believe to be reliable and correct, but accuracy and completeness of said tests are not guaranteed and are not to be construed as a warranty either expressed or implied. User shall rely on his or her own information and tests to determine suitability of the product for the intended use and user assumes all risk and liability resulting from his or her use of the product. Nothing contained in any supplied materials relieves the user of the obligation to read and follow the warnings and instructions for each product as set forth in the current Technical Data Sheet, product label and Safety Data Sheet prior to product use away.



CORMART HOUSE, Plot A, Block 2,  
 Ilupeju Industrial Estate  
 Apapa-Oworonshoki Expressway  
 Lagos, Nigeria  
 +234 907 005 8058  
 cormart@clicktgi.net

