

# Waterproofing

## Liquid applied & preformed membranes for waterproofing of structures

Product	Description	Typical Uses	Dosage/ Coverage/yield
<b>Proofex Engage</b>	Pre-applied waterproofing membrane conforming to the requirements of BS EN 13967:2004 and BS8102:2009. Proofex Engage mechanically bonds to poured concrete, remaining in place if settlement of substrate occurs	Critical & deep basements, durable, simple application, inert product, resistant to chemicals and aggressive ground salts.	Refer to datasheet
<b>Proofex GP</b> 20 and 200 litres	Proofex GP is a cold applied self-adhesive sheet membrane comprising of a polymer modified bitumen layer internally reinforced, bonded on to an outer surface of polyethylene film. The polymer bitumen adhesive layer is protected on the underside by a silicone release paper which is removed just prior to the application of Proofex GP to the tack coat primed substrate.	To provide a continuously bonded waterproof membrane for building and civil engineering structures.	Refer to datasheet
<b>Supercast PVC</b> 20 & 200 litre drums	Nitoproof 10 is a brown/ black liquid blend of selected bitumens emulsified with water to give an easily applied protective coating.	To act as a damp-proof membrane and vapour seal for concrete and masonry. It can also be used as a protective coating for concrete below ground	Refer datasheet
<b>Polyurea WCS</b>	Fast setting, pure polyuria elastomeric waterproof coating	Standard grade offers an anti-corrosion, waterproof and protective coating for small areas and repairs of polyurea coatings, on concrete and steel surfaces. Gun Grade offers an excellent seam seal for the Fosroc Proofex Engage waterproofing system.	Refer datasheet

